

Evolutionary Architecture Search for Chlorophyll-*a* Prediction in Lakes using Sentinel-2

Kürşat Kömürcü^{1, 2, 3} Linas Petkevičius¹

¹Vilnius University, Institute of Computer Science, Artificial Intelligence Methods Lab

²IRISA, Université Bretagne Sud

³European Commission Joint Research Center

Abstract Small tabular datasets with expert-designed spectral features are the norm in operational Earth observation, and the networks applied to them are typically hand-designed. We revisit one such published model – a Sentinel-2 algal bloom classifier – and ask what architecture search adds, holding the task, the features and the lake-level train/test split of the original study fixed. Searching an extended multilayer-perceptron space with regularized evolution, and selecting on inner-cross-validation AUC only, we find networks that improve held-out AUC from 0.790 to 0.820 and accuracy from 0.733 to 0.748 while using 409 trainable parameters, 26 times fewer than the strongest hand-designed reference. The search converges on a consistent recipe – a single narrow layer, RMS normalisation, tanh activation, step-decayed RMSprop and weight averaging – that a practitioner would be unlikely to reach by default. At 1.6 kB the resulting model is small enough to serve as an onboard screening trigger, which is the setting that motivates the work. Code: <https://github.com/VU-AI/ML/automl4eo-bloom-nas>.

1 Introduction

Operational Earth observation tasks are frequently small and tabular: in-situ labels are expensive, so datasets run to a few thousand rows of expert-designed spectral features rather than to millions of images. The networks applied to them are correspondingly hand-designed, as remains common for tabular problems generally (Gorishniy et al., 2021; Grinsztajn et al., 2022). Neural architecture search is a mature toolbox (Elsken et al., 2019), but is applied overwhelmingly to large-scale vision; its behaviour in this regime is much less characterised, and it is not obvious that a search should help at all when the task offers so little signal to search against.

We study it on one such task. Grendaitė and Petkevičius (2024) assembled a dataset of Baltic lakes matching in-situ observations to Sentinel-2 overpasses and trained a family of hand-designed networks – plain stacks, residual stacks, and stacks with parallel dense heads – on per-lake spectral features, reporting 71.6 % accuracy for bloom classification. Holding their task, features and lake-level split fixed, we ask what architecture search adds.

The question matters beyond accuracy. Downlink bandwidth rather than sensing is the binding constraint for many Earth observation products, and onboard inference has been demonstrated in orbit as a way to transmit only informative data (Giuffrida et al., 2020, 2022; Marin et al., 2021). How small a competitive model can be is therefore an operational question, not only an efficiency one.

We search an extended multilayer-perceptron (MLP) space with regularized evolution, selecting on inner-cross-validation AUC alone. Our contributions are:

- Searched architectures that outperform all three hand-designed reference networks on held-out AUC, accuracy and F_1 , with all ten highest-ranked configurations beating every baseline on AUC.

- A 409-parameter model – 26 to 47 times smaller than the references – that achieves this, making onboard screening plausible at 1.6 kB.
- A characterisation of the design region the search converges on, and an account of why selection must be driven by AUC at this sample size.

2 Task, data and protocol

Data. The dataset released with Grendaitė and Petkevičius (2024) contains 1151 observations from 429 monitoring sites in Lithuania, Latvia and Estonia, collected between 2017 and 2021.¹ Each row holds Sentinel-2 surface reflectances together with derived radiometric indices of the kind established for chlorophyll retrieval in turbid inland waters (Mishra and Mishra, 2012), for one lake on one date, with a binary bloom label. Classes are close to balanced (624 non-bloom, 527 bloom), so accuracy is interpretable against a 52.9 % majority-class floor. We use the same 14 features as the reference study.

Split. We reproduce the reference split exactly, including its random seed: 70 % of the unique site codes are drawn for training and every measurement from a selected lake follows, giving 801 training and 350 test rows over 129 held-out lakes. Grouping by lake rather than by row is essential here, since a single lake contributes up to 17 observations and row-level splitting would allow a model to memorise individual water bodies.

Nested evaluation. All search signal comes from a lake-grouped 5-fold cross-validation *inside* the 801-row training split; the 350-row test split is opened once, after the search has terminated. This nesting is not a formality at this scale: selecting the best of thousands of candidates on the same data used to report performance yields the maximum of a noisy statistic rather than a generalisation estimate, and the resulting optimism can rival the differences between the methods compared (Varma and Simon, 2006; Cawley and Talbot, 2010).

Selection metric. We select on AUC rather than accuracy, for two reasons. Operationally, an onboard trigger ranks candidate scenes against a transmission budget, so the decision threshold is a deployment parameter rather than a property of the model. Empirically, accuracy on a 160-row validation fold is dominated by how a handful of near-threshold observations happen to fall, whereas AUC uses the full ordering: the seed-to-seed standard deviation of held-out accuracy reaches 0.019 in our runs while that of AUC stays at or below 0.008. Since the variance of the selection criterion, not only its bias, governs how badly model selection overfits (Cawley and Talbot, 2010), this choice does more work than the metric definition alone suggests.

3 Search space and method

Space. The space (Table 1) stays within the MLP family, so that the comparison against the hand-designed networks is like-for-like, but widens the axes those networks left implicit; it contains all three reference architectures as individual points. Five block types are available: plain dense blocks, residual blocks, the parallel-dense “multi-head” block used in the reference implementation, gated linear units, and gated residual blocks, the last two following components that have proved useful in tabular deep learning (Gorishniy et al., 2021). Width is specified by a base width together with a profile, since the reference networks use tapering stacks that a single global width cannot express. Optimiser, schedule, warmup, label smoothing, class weighting, gradient clipping and weight averaging (Izmailov et al., 2018) are searched alongside the topology. Candidates above 200k trainable parameters are rejected: with 801 training rows, larger networks cannot be constrained by the data, and the onboard setting rules them out regardless.

¹The public release appears to predate the revision referenced by the accompanying preprocessing script, so our baseline numbers are a reimplement on the public data rather than a bit-exact reproduction of the published figures.

Table 1: Search space, approximately 10^{12} configurations before the parameter-budget constraint.

Dimension	Values	Dimension	Values
Blocks	1–6	Optimiser	AdamW, Adam, SGD, RMSprop
Base width	16–256 (9 values)	Learning rate	10^{-4} – 3×10^{-2}
Width profile	constant, taper, expand, hourglass	Schedule	constant, cosine, step
Block type	plain, residual, multi-head, GLU, GRN	Warmup fraction	0.0, 0.05, 0.1
Heads	2, 4, 8	Weight decay	0 – 10^{-2}
Normalisation	batch, layer, RMS, none	Batch size	8–256
Activation	ReLU, GELU, ELU, SiLU, Mish, tanh	Epochs	50–600
Dropout	0.0–0.5	Label smoothing	0.0–0.15
Input dropout	0.0–0.3	Class weighting	off, on
		Gradient clip	off, 0.5, 1.0, 5.0
		Weight EMA	off, 0.99, 0.995, 0.999

Table 2: Held-out performance, mean $\pm$ standard deviation over 10 weight seeds. Selection used inner-CV AUC only. NAS-1/6/8 are the three highest-ranked distinct architectures; the remaining seven of the top ten fall within 0.002 AUC of these.

Model	CV AUC	Test AUC	Test acc.	F_1	Params
Baseline-MLP	0.8055	0.7902 $\pm$.006	0.7306 $\pm$.009	0.7241	10 625
Baseline-Res	0.7588	0.7543 $\pm$.010	0.6989 $\pm$.010	0.6746	32 129
Baseline-MHA	0.7914	0.7785 $\pm$.008	0.7329 $\pm$.011	0.7266	19 073
NAS-1	0.8240	0.8181 $\pm$.001	0.7460 $\pm$.004	0.7442	409
NAS-6	0.8238	0.8203 $\pm$.001	0.7449 $\pm$.003	0.7449	433
NAS-8	0.8237	0.8187 $\pm$.001	0.7483 $\pm$.003	0.7466	409

Method. Random search is a strong default in spaces of this kind (Bergstra and Bengio, 2012; Li and Talwalkar, 2019) and we used it in preliminary work, but the space above is roughly a trillion configurations and rewards local exploitation. We therefore use regularized evolution (Real et al., 2019): an initial random population of 64, then rounds in which 20 children are bred by tournament selection (size 10) and one to three random dimension edits, with the oldest individuals retired regardless of score. Age-based rather than score-based retirement is the important detail at this scale: a single cross-validation estimate carries one to three points of standard deviation, so a configuration can enter the population through luck, and score-based retirement would let it persist indefinitely while its mutations took over. Retirement by age forces a lineage to re-earn its score at every generation.

Each candidate is scored by 5 folds $\times$ 3 weight seeds, averaged. The run evaluated 2720 candidates (1827 distinct architectures after collapsing configurations that differ only in inactive dimensions) in approximately five hours on 20 CPU cores. The networks are small enough that CPU evaluation parallelised across trials is faster than GPU execution.

4 Results

Table 2 reports the comparison. To ensure that any gain is attributable to the searched configuration rather than to an incidentally better training loop, the reference architectures are expressed in the same space and trained by the same code, using the optimiser and schedule settings of the original implementation.

The searched models improve held-out AUC by 3.0 points over the best baseline and accuracy by 1.5 points, using 409 parameters against 10 625 for the strongest reference network – a 26-fold

reduction, or 47-fold against the multi-head variant. All ten highest-ranked configurations beat every baseline on AUC, so the result does not rest on a single fortunate candidate.

The searched models are also markedly more stable, with a seed-to-seed standard deviation of 0.001 in AUC against 0.006–0.010 for the baselines, which we attribute to the weight averaging the search selected (Izmailov et al., 2018). The optimism of the cross-validation estimate – the gap between inner-CV and held-out AUC – is only 0.006 for the selected models, indicating that selection on AUC at this budget is not materially inflated by the selection bias Cawley and Talbot (2010) describe.

What the search converged on. Among the 100 highest-ranked configurations, several choices are unanimous: plain dense blocks, RMSprop, step decay, RMS normalisation, tanh activation, weight EMA with decay 0.999, and class weighting. The median configuration uses a single layer of width 24 trained for 300 epochs. Three of these sit away from what a practitioner would pick by default. The tanh activation has largely been displaced by ReLU-family functions, yet it is bounded, which limits how confidently a small network can commit on the 801 training rows available. Weight averaging plays a similar role and is the main source of the stability noted above. Most strikingly, the search settles on a single hidden layer: the depth of the reference networks is not merely unnecessary but actively unhelpful at this sample size. We did not anticipate this combination, which is the argument for searching rather than designing.

5 Discussion: onboard feasibility

At 409 parameters the selected model occupies 1.6 kB in float32 and requires on the order of 400 multiply-accumulates per lake. On the class of processor flown in onboard-AI demonstrations (Giuffrida et al., 2022) this cost is negligible, and the model could screen candidate observations in orbit so that only lakes flagged as blooming consume downlink capacity – the same argument that motivated onboard cloud rejection (Giuffrida et al., 2020).

We should be precise about what this does and does not establish. The features used here derive from atmospherically corrected Level-2A products computed on the ground, together with water masking; porting that chain to the satellite is a separate and harder problem (Marin et al., 2021). What our result establishes is that the *decision layer* of such a pipeline is essentially free, and that the capacity a hand-designed model spends on it can be reduced by more than an order of magnitude at no cost – indeed with a gain.

6 Limitations and future work

The evaluation rests on one dataset and one train/test split. We preserved the reference split deliberately, for comparability, but a single 350-row test split carries roughly 2.4 points of standard error on accuracy, and we have not measured how the ranking behaves across resampled lake splits. The public data release also appears to predate the revision used for the published numbers, so our baselines are a reimplement rather than an exact reproduction. The search itself converged narrowly: the ten highest-ranked configurations are minor variations of one architecture, and duplicate suppression with periodic random re-injection would characterise the space more broadly.

Three extensions follow naturally: the same protocol applied to the chlorophyll-*a* regression task released with the reference study; feature selection as a search dimension, which is operationally relevant since reading fewer bands means less onboard processing; and quantisation-aware search, which would turn the onboard claim from a parameter count into a measured latency and energy figure on representative hardware.

References

Bergstra, J. and Bengio, Y. (2012). Random search for hyper-parameter optimization. *Journal of Machine Learning Research*, 13:281–305.

- Cawley, G. C. and Talbot, N. L. C. (2010). On over-fitting in model selection and subsequent selection bias in performance evaluation. *Journal of Machine Learning Research*, 11:2079–2107.
- Elsken, T., Metzen, J. H., and Hutter, F. (2019). Neural architecture search: A survey. *Journal of Machine Learning Research*, 20(55):1–21.
- Giuffrida, G., Diana, L., de Gioia, F., Benelli, G., Meoni, G., Donati, M., and Fanucci, L. (2020). CloudScout: A deep neural network for on-board cloud detection on hyperspectral images. *Remote Sensing*, 12(14):2205.
- Giuffrida, G., Fanucci, L., Meoni, G., Batič, M., Buckley, L., Dunne, A., van Dijk, C., Esposito, M., Hefe, J., Vercruyssen, N., Furano, G., Pastena, M., and Aschbacher, J. (2022). The ϕ -sat-1 mission: The first on-board deep neural network demonstrator for satellite Earth observation. *IEEE Transactions on Geoscience and Remote Sensing*, 60:1–14.
- Gorishniy, Y., Rubachev, I., Khrulkov, V., and Babenko, A. (2021). Revisiting deep learning models for tabular data. In *Advances in Neural Information Processing Systems*, volume 34, pages 18932–18943.
- Grendaitė, D. and Petkevičius, L. (2024). Identification of algal blooms in lakes in the Baltic states using Sentinel-2 data and artificial neural networks. *IEEE Access*, 12:27973–27988.
- Grinsztajn, L., Oyallon, E., and Varoquaux, G. (2022). Why do tree-based models still outperform deep learning on typical tabular data? In *Advances in Neural Information Processing Systems*, volume 35, pages 507–520.
- Izmailov, P., Podoprikin, D., Garipov, T., Vetrov, D., and Wilson, A. G. (2018). Averaging weights leads to wider optima and better generalization. In *Proceedings of the 34th Conference on Uncertainty in Artificial Intelligence (UAI)*, pages 876–885.
- Li, L. and Talwalkar, A. (2019). Random search and reproducibility for neural architecture search. *arXiv preprint arXiv:1902.07638*.
- Marin, A., Coelho, C., Deconinck, F., Babkina, I., Longépé, N., and Pastena, M. (2021). Φ -Sat-2: Onboard AI apps for Earth observation. *Proceedings of Space Artificial Intelligence*.
- Mishra, S. and Mishra, D. R. (2012). Normalized difference chlorophyll index: A novel model for remote estimation of chlorophyll-a concentration in turbid productive waters. *Remote Sensing of Environment*, 117:394–406.
- Real, E., Aggarwal, A., Huang, Y., and Le, Q. V. (2019). Regularized evolution for image classifier architecture search. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 4780–4789.
- Varma, S. and Simon, R. (2006). Bias in error estimation when using cross-validation for model selection. *BMC Bioinformatics*, 7(91).